


Lists and Sequences





Outline and Reading

- ◆ Singly linked list
- ◆ Position ADT and List ADT (§2.2.2)
- ◆ Doubly linked list (§ 2.2.2)
- ◆ Sequence ADT (§ 2.2.3)
- ◆ Implementations of the sequence ADT (§ 2.2.3)
- ◆ Iterators (2.2.3)


Singly Linked List

- ◆ A singly linked list is a concrete data structure consisting of a sequence of nodes
- ◆ Each node stores
 - element
 - link to the next node




Stack with a Singly Linked List

- ◆ We can implement a stack with a singly linked list
- ◆ The top element is stored at the first node of the list
- ◆ The space used is $O(n)$ and each operation of the Stack ADT takes $O(1)$ time



Queue with a Singly Linked List

- ◆ We can implement a queue with a singly linked list
 - The front element is stored at the first node
 - The rear element is stored at the last node
- ◆ The space used is $O(n)$ and each operation of the Queue ADT takes $O(1)$ time



Position ADT

- ◆ The **Position** ADT models the notion of place within a data structure where a single object is stored
- ◆ It gives a unified view of diverse ways of storing data, such as
 - a cell of an array
 - a node of a linked list
- ◆ Just one method:
 - object **element()**: returns the element stored at the position

List ADT

- ◆ The **List** ADT models a sequence of positions storing arbitrary objects
- ◆ It establishes a before/after relation between positions
- ◆ Generic methods:
 - **size()**, **isEmpty()**
- ◆ Query methods:
 - **isFirst(p)**, **isLast(p)**

Accessor methods:



- **first()**, **last()**
- **before(p)**, **after(p)**

Update methods:

- **replaceElement(p, o)**, **swapElements(p, q)**
- **insertBefore(p, o)**, **insertAfter(p, o)**,
- **insertFirst(o)**, **insertLast(o)**
- **remove(p)**


Doubly Linked List

- ◆ A doubly linked list provides a natural implementation of the List ADT
- ◆ Nodes implement Position and store:
 - element
 - link to the previous node
 - link to the next node
- ◆ Special trailer and header nodes




Insertion

- ◆ We visualize operation `insertAfter(p, X)`, which returns position `q`



Deletion

◆ We visualize `remove(p)`, where `p = last()`



Performance

- ◆ In the implementation of the List ADT by means of a doubly linked list
 - The space used by a list with n elements is $O(n)$
 - The space used by each position of the list is $O(1)$
 - All the operations of the List ADT run in $O(1)$ time
 - Operation `element()` of the Position ADT runs in $O(1)$ time

Sequence ADT


- ◆ The **Sequence** ADT is the union of the Vector and List ADTs
- ◆ Elements accessed by
 - Rank, or
 - Position
- ◆ Generic methods:
 - `size()`, `isEmpty()`
- ◆ Vector-based methods:
 - `elemAtRank(r)`,
`replaceAtRank(r, o)`,
`insertAtRank(r, o)`,
`removeAtRank(r)`
- ◆ List-based methods:
 - `first()`, `last()`,
`before(p)`, `after(p)`,
`replaceElement(p, o)`,
`swapElements(p, q)`,
`insertBefore(p, o)`,
`insertAfter(p, o)`,
`insertFirst(o)`,
`insertLast(o)`,
`remove(p)`
- ◆ Bridge methods:
 - `atRank(r)`, `rankOf(p)`

Applications of Sequences

- ◆ The Sequence ADT is a basic, general-purpose, data structure for storing an ordered collection of elements
- ◆ Direct applications:
 - Generic replacement for stack, queue, vector, or list
 - small database (e.g., address book)
- ◆ Indirect applications:
 - Building block of more complex data structures

Array-based Implementation

- ◆ We use a circular array storing positions
- ◆ A position object stores:
 - Element
 - Rank
- ◆ Indices f and l keep track of first and last positions



Sequence Implementations

Operation	Array	List
size, isEmpty	1	1
atRank, rankOf, elemAtRank	1	<i>n</i>
first, last, before, after	1	1
replaceElement, swapElements	1	1
replaceAtRank	1	<i>n</i>
insertAtRank, removeAtRank	<i>n</i>	<i>n</i>
insertFirst, insertLast	1	1
insertAfter, insertBefore	<i>n</i>	1
remove	<i>n</i>	1

Iterators

- ◆ An iterator abstracts the process of scanning through a collection of elements
- ◆ Methods of the ObjectIterator ADT:
 - object `object()`
 - boolean `hasNext()`
 - object `nextObject()`
 - `reset()`
- ◆ Extends the concept of Position by adding a traversal capability
- ◆ Implementation with an array or singly linked list
- ◆ An iterator is typically associated with an another data structure
- ◆ We can augment the Stack, Queue, Vector, List and Sequence ADTs with method:
 - ObjectIterator `elements()`
- ◆ Two notions of iterator:
 - snapshot: freezes the contents of the data structure at a given time
 - dynamic: follows changes to the data structure